

L.A. FOAM AIR FILTER OIL, 300G AEROSOL

Chemwatch Independent Material Safety Data Sheet

Issue Date: 16-Feb-2012

9317SP

CHEMWATCH 30-4032

Version No:2.0

CD 2012/1 Page 1 of 7

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

L.A. FOAM AIR FILTER OIL, 300G AEROSOL

PROPER SHIPPING NAME

AEROSOLS

PRODUCT USE

Foam air filter oil spray.

SUPPLIER

Company: JJETT Pty Ltd

Address:

84 Camp Road

Broadmeadows

VIC, 3047

Australia

Telephone: +61 3 9457 1125

Fax: +61 3 9459 7978

Email: sales@aerosolve.com.au

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

DANGEROUS GOODS. NON-HAZARDOUS SUBSTANCE. According to the ADG Code and NOHSC Criteria.

RISK

Risk Codes

R12

R44

Risk Phrases

- Extremely flammable.
- Risk of explosion if heated under confinement.

SAFETY

Safety Codes

S16

S23

S24

S25

S37

S39

S26

Safety Phrases

- Keep away from sources of ignition. No smoking.
- Do not breathe gas/fumes/vapour/spray.
- Avoid contact with skin.
- Avoid contact with eyes.
- Wear suitable gloves.
- Wear eye/face protection.
- In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.
- This material and its container must be disposed of as hazardous waste.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
hydrocarbons non- hazardous		Not Spec
ingredients non- hazardous		Not Spec
hydrocarbon propellant	68476-85-7.	Not Spec

Section 4 - FIRST AID MEASURES

SWALLOWED

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.

continued...

L.A. FOAM AIR FILTER OIL, 300G AEROSOL

Chemwatch Independent Material Safety Data Sheet

Issue Date: 16-Feb-2012

9317SP

CHEMWATCH 30-4032

Version No:2.0

CD 2012/1 Page 2 of 7

Section 4 - FIRST AID MEASURES

- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.

EYE

- If aerosols come in contact with the eyes:
 - Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - Transport to hospital or doctor without delay.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If solids or aerosol mists are deposited upon the skin:
 - Flush skin and hair with running water (and soap if available).
 - Remove any adhering solids with industrial skin cleansing cream.
 - DO NOT use solvents.
 - Seek medical attention in the event of irritation.

INHALED

- If aerosols, fumes or combustion products are inhaled:
 - Remove to fresh air.
 - Lay patient down. Keep warm and rested.
 - Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
 - If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

NOTES TO PHYSICIAN

- Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- SMALL FIRE:
 - Water spray, dry chemical or CO₂
- LARGE FIRE:
 - Water spray or fog.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.

FIRE/EXPLOSION HAZARD

- Liquid and vapour are highly flammable.
 - Severe fire hazard when exposed to heat or flame.
 - Vapour forms an explosive mixture with air.
 - Severe explosion hazard, in the form of vapour, when exposed to flame or spark.
- Combustion products include: carbon dioxide (CO₂), other pyrolysis products typical of burning organic material.

FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

HAZCHEM

2YE

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Wear protective clothing, impervious gloves and safety glasses.
- Shut off all possible sources of ignition and increase ventilation.

continued...

L.A. FOAM AIR FILTER OIL, 300G AEROSOL

Chemwatch Independent Material Safety Data Sheet

Issue Date: 16-Feb-2012

9317SP

CHEMWATCH 30-4032

Version No:2.0

CD 2012/1 Page 3 of 7

Section 6 - ACCIDENTAL RELEASE MEASURES

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

SUITABLE CONTAINER

- Aerosol dispenser.
- Check that containers are clearly labelled.

STORAGE INCOMPATIBILITY

- Avoid storage with oxidisers.

STORAGE REQUIREMENTS

- Store below 38 deg. C.
- Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can.
- Store in original containers in approved flammable liquid storage area.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- No smoking, naked lights, heat or ignition sources.
- Keep containers securely sealed. Contents under pressure.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³
Australia Exposure Standards	L.A. Foam Air Filter Oil, 300g Aerosol (LPG (liquified petroleum gas))	1000	1800

MATERIAL DATA

L.A. FOAM AIR FILTER OIL, 300G AEROSOL:

- None assigned. Refer to individual constituents.

HYDROCARBON PROPELLANT:

- For butane:

Odour Threshold Value: 2591 ppm (recognition)

Butane in common with other homologues in the straight chain saturated aliphatic hydrocarbon series is not characterised by its toxicity but by its narcosis-inducing effects at high concentrations. The TLV is based on analogy with pentane by comparing their lower explosive limits in air.

Odour Safety Factor(OSF)

OSF=0.22 (n-BUTANE).

For propane

Odour Safety Factor(OSF)

OSF=0.16 (PROPANE).

PERSONAL PROTECTION

continued...

L.A. FOAM AIR FILTER OIL, 300G AEROSOL

Chemwatch Independent Material Safety Data Sheet

Issue Date: 16-Feb-2012

9317SP

CHEMWATCH 30-4032

Version No:2.0

CD 2012/1 Page 4 of 7

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATOR

- Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

EYE

- No special equipment for minor exposure i.e. when handling small quantities.

OTHERWISE: For potentially moderate or heavy exposures:

- Safety glasses with side shields.
- NOTE: Contact lenses pose a special hazard; soft lenses may absorb irritants and ALL lenses concentrate them.

HANDS/FEET

- No special equipment needed when handling small quantities.
- OTHERWISE:
- For potentially moderate exposures:
- Wear general protective gloves, eg. light weight rubber gloves.

OTHER

- No special equipment needed when handling small quantities.

OTHERWISE:

- Overalls.
- Skin cleansing cream.
- Eyewash unit.
- Do not spray on hot surfaces.
- The clothing worn by process operators insulated from earth may develop static charges far higher (up to 100 times) than the minimum ignition energies for various flammable gas-air mixtures. This holds true for a wide range of clothing materials including cotton.
- Avoid dangerous levels of charge by ensuring a low resistivity of the surface material worn outermost.

BRETHERRICK: Handbook of Reactive Chemical Hazards.

ENGINEERING CONTROLS

- Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

- Supplied as an aerosol pack. Contents under PRESSURE.
- Coloured oily liquid; does not mix with water.

PHYSICAL PROPERTIES

Gas.

Does not mix with water.

Floats on water.

State	COMPRESSED GAS	Molecular Weight	Not Applicable
Melting Range (°C)	Not Available	Viscosity	Not Available
Boiling Range (°C)	Not Available	Solubility in water (g/L)	Immiscible
Flash Point (°C)	- 81 propellant	pH (1% solution)	Not Applicable
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Applicable
Autoignition Temp (°C)	Not Available	Vapour Pressure (kPa)	379
Upper Explosive Limit (%)	7.5	Specific Gravity (water=1)	0.85
Lower Explosive Limit (%)	1.2	Relative Vapour Density (air=1)	Not Available
Volatile Component (%vol)	~90	Evaporation Rate	Not Available

Section 10 - STABILITY AND REACTIVITY

CONDITIONS CONTRIBUTING TO INSTABILITY

- Elevated temperatures.
- Presence of open flame.
- Product is considered stable.
- Hazardous polymerisation will not occur.

continued...

L.A. FOAM AIR FILTER OIL, 300G AEROSOL

Chemwatch Independent Material Safety Data Sheet
Issue Date: 16-Feb-2012
9317SP

CHEMWATCH 30-4032
Version No:2.0
CD 2012/1 Page 5 of 7
Section 10 - STABILITY AND REACTIVITY

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

- Accidental ingestion of the material may be damaging to the health of the individual. Ingestion may result in nausea, abdominal irritation, pain and vomiting.

EYE

- There is some evidence to suggest that this material can cause eye irritation and damage in some persons.

SKIN

- There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. The material may accentuate any pre-existing dermatitis condition.

INHALED

- Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination. If exposure to highly concentrated solvent atmosphere is prolonged this may lead to narcosis, unconsciousness, even coma and possible death.
WARNING: Intentional misuse by concentrating/inhaling contents may be lethal.

CHRONIC HEALTH EFFECTS

- Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

TOXICITY AND IRRITATION

- Not available. Refer to individual constituents.

Section 12 - ECOLOGICAL INFORMATION

This material and its container must be disposed of as hazardous waste.

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
hydrocarbon propellant	No Data Available	No Data Available		

Section 13 - DISPOSAL CONSIDERATIONS

- Consult State Land Waste Management Authority for disposal.
- Discharge contents of damaged aerosol cans at an approved site.
- Allow small quantities to evaporate.
- DO NOT incinerate or puncture aerosol cans.

Section 14 - TRANSPORTATION INFORMATION



Labels Required: FLAMMABLE GAS

continued...

L.A. FOAM AIR FILTER OIL, 300G AEROSOL

Chemwatch Independent Material Safety Data Sheet

Issue Date: 16-Feb-2012

9317SP

CHEMWATCH 30-4032

Version No:2.0

CD 2012/1 Page 6 of 7

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM:

2YE (ADG7)

ADG7:

Class or Division	2.1	Subsidiary Risk:	None
UN No.:	1950	Packing Group:	None
Special Provision:	63 190 277 327	Limited Quantity:	None
Portable Tanks & Bulk Containers - Instruction:	None	Portable Tanks & Bulk Containers - Special Provision:	None
Packagings & IBCs - Packing Instruction:	None	Packagings & IBCs - Special Packing Provision:	P003 LP02

Name and Description: None

Air Transport IATA:

ICAO/IATA Class:	2.1	ICAO/IATA Subrisk:	None
UN/ID Number:	1950	Packing Group:	-
Special provisions:	A145		

Shipping name:AEROSOLS

Maritime Transport IMDG:

IMDG Class:	2	IMDG Subrisk:	SP63
UN Number:	1950	Packing Group:	None
EMS Number:	F- D, S- U	Special provisions:	63 190 277 327 344 959
Limited Quantities:	See SP277		
Shipping name:AEROSOLS			

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: UN

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE None

REGULATIONS

Regulations for ingredients

hydrocarbon propellant (CAS: 68476-85-7,68476-86-8) is found on the following regulatory lists;

"Australia Exposure Standards", "Australia Hazardous Substances", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "International Council of Chemical Associations (ICCA) - High Production Volume List"

No data for L.A. Foam Air Filter Oil, 300g Aerosol (CW: 30-4032)

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
hydrocarbon propellant	68476- 85- 7, 68476- 86- 8

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 16-Feb-2012

continued...

L.A. FOAM AIR FILTER OIL, 300G AEROSOL

Chemwatch Independent Material Safety Data Sheet

Issue Date: 16-Feb-2012

9317SP

CHEMWATCH 30-4032

Version No:2.0

CD 2012/1 Page 7 of 7

Section 16 - OTHER INFORMATION

Print Date: 16-Feb-2012

This is the end of the MSDS.