

MATERIAL SAFETY DATA SHEET

SECTION 1 – MATERIAL IDENTIFICATION AND INFORMATION

Product Identity: Prevent-A-Flat
Manufacturers Name: Kleenskin Products Pty. Ltd.
Address: 53 Crusoe Road Kangaroo Flat Vic. 3555
Telephone: 02-80808361

Effective Date: January 2005
Revised Date: January 2103

Product Type: Water Based Tyre Sealant
DOT Classification: Not Regulated
Product Application:
Preventative maintenance compound which helps seal punctures in tread area, bead leaks and distribute heat in tyres to prolong service life.

SECTION 11 – INGREDIENTS

Components	Hazardous %	TLV (Units)	Prod. CAS#
Propylene Glycol	20%	50ppm	107-21-1
Cellose QP-100 MH	N/A	N/A	9004-62-0
Demineralised Water	N/A	N/A	7732-18-5
Dyes & Bacteriacide	N/A	N/A	67-56-1
Antioxidant and Anti-rust	0.5%	N/A	149-57-5

SECTION 111 PHYSICAL DATA

Product Description: Colloidal Suspension
Water Solubility: 90%
Boiling Point: +150 degrees Celsius @ 45kpa
Freezing Point: -50 degrees Celsius
Melting Point: Liquid at room temperature
Density: 1.1 @ 15 degrees Celsius
pH: 7.6

SECTION IV – FIRE & EXPLOSION HAZARD DATA

Nil – Not Flammable

SECTION V – HEALTH HAZARD DATA

Oral:	Slight Toxic
Dermal:	Non toxic
Inhalation:	Slight toxicity
Eye	Slightly irritant

EMERGENCY AND FIRST AID PROCEDURES

Eye contact:	Flush with water
Skin contact:	Flush with water
Inhalation:	Remove to fresh air
Ingestion:	Contact medico re: Propylene Glycol ingestion Westmead Hospital Tel. 13 1126

REACTIVITY DATA:

Concurrent presence of powerful oxidants and high heat may produce carbon monoxide gas.

<u>SPILLAGE PROCEDURE</u>	Absorb with sand/sawdust and bury.
----------------------------------	---

We believe all information above is accurate and is offered in good faith but without guarantee. Since conditions of use and suitability of the product covered herein for particular uses are beyond our control, all risks of application of the product described herein are assumed by the user. Nothing herein is to be construed as a recommendation for uses which infringe valid patents or as extending licence under valid patents.

Where the information provided herein discloses a potential hazard or hazardous component, adequate warning should be given to employees and users, and appropriate precautions taken, including the practice of sound industrial hygiene.